



Newland Express Transport Ltd

Hazardous Substances Risk Assessment

| | | | |
|------------------------|-------------------------------|--------------------|-----------------|
| Title | COSHH | Date Of Assessment | Thu 15 Jan 2026 |
| Site | Newland Express Transport Ltd | Location | Warehouse/yard. |
| Risk Assessor | James Asbrey | Assisted by | – |
| Non-Employees Involved | – | | |
| Review date | Fri 15 Jan 2027 | Reviewer | James Asbrey |

Substance

| | |
|--|--|
| Substance Name | Fasttrack |
| Supplier | Kaap International |
| Date of Safety Data Sheet (SDS) | Fri 01 Jan 2021 |
| Details of Use | Used occasionally in small amounts to lubricate the runners for the curtains on vehicles. Task takes no longer than 5 minutes per curtain. |
| Are there any hazard symbols on the SDS? | Yes |
| Associated hazards | Hazard |
| |  Flammable |
| |  Caution |



Hazardous to the aquatic environment



Longer term health hazards

Hazard Codes & Statements**Code****Description**

H222

Extremely flammable aerosol

H336

May cause drowsiness or dizziness

H373

See SDS

H411

Toxic to aquatic life with long lasting effects

H229

Pressurised container: May burst if heated

Precaution Codes & Statements

P102

Keep out of reach of children

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211

Do not spray on an open flame or other ignition source

P251

Do not pierce or burn, even after use

P261

See SDS

P270

Do not eat, drink or smoke when using this product

P271

Use only outdoors or in a well ventilated area

P280

See SDS

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F

P501

See SDS

| | | |
|---|---|---|
| | P304+ P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing |
| | P312 | See SDS |
| | P391 | Collect spillage |
| | P403 + P233 | Store in a well ventilated place. Keep container tightly closed |
| | P405 | Store locked up |
| Does this substance have workplace exposure limits? | Yes | |
| Short term | Butane 15min wel 750ppm 1810mg/m3, Butylacetate 15min wel 200ppm 966mg/m3, Mineral Oil 15min wel 10mg/m3. | |
| Long term | Naptha 8 hour wel 1000mg/m3, White Spirit 8 hour wel 600mg/m3. | |
| Is Health Surveillance required? | No | |
| Routes of entry into body | Absorption (through skin/eyes), Inhalation (breathing in) | |

Assessment

| | |
|---|--------------------|
| How much is being used per batch? | Small (<1KG or 1L) |
| Is the substance use a solid or liquid? | Liquid |
| How volatile is the liquid? | Medium |
| Hazard group | C |
| Control system | Containment |

Hazardous substances control system

| | |
|-----------------|-----------------|
| Control Measure | Further Details |
|-----------------|-----------------|

Control measures

| Existing Control Measures | Description |
|---------------------------|---|
| | PPE supplied and used at all times, only small amounts used in well ventilated areas. |

Past reviews

| Review date | Reviewer | Comments |
|-------------|----------|----------|
|-------------|----------|----------|